

PZKL... Cover

Overview:

Application

Cable protection against damage.
Used in heavy dust indoor conditions.

Material


Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:

F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG) for 1mm thick min

E- stainless steel (SS) to 1.2mm thick max.

L- powder coating in a full range of colours (PC)



Cover with a lock

Important! Made to order covers are 2m long. Covers PKP and PZKP

are not manufactured from stainless steel (SS).

NOTE:

Up to 100mm WIDE - 1 LOCK - SYMMETRICALLY
OVER 100mm WIDE - 2 LOCKS

Versions:

Sheet thickness: **0,7 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight 1 pc.
PZKL50/2	2000	50	101505	20	0,47
PZKL50/3	3000	50	101605	20	0,47
PZKL100/2	2000	100	101510	10	0,77
PZKL100/3	3000	100	101610	10	0,77
PZKL150/2	2000	150	101515	6	1,07
PZKL150/3	3000	150	101615	6	1,07
PZKL200/2	2000	200	101520	6	1,37
PZKL200/3	3000	200	101620	6	1,37
PZKL300/2	2000	300	101530	4	1,97
PZKL300/3	3000	300	101630	4	1,97
PZKL400/2	2000	400	101140	4	2,57
PZKL400/3	3000	400	101240	4	2,57
PZKL500/2	2000	500	101150	2	3,17
PZKL500/3	3000	500	101250	2	3,17
PZKL600/2	2000	600	101160	2	3,77
PZKL600/3	3000	600	101260	2	3,77

Connected products:

