



KSP...H100N Cable Tray

Overview:

Application

Cable routing in halls or on-site with limited number of supporting structures. High tray durability allows for applying spacing of supports even every 6m.



Material

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:

F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)
E- stainless steel (SS)
L- powder coating in a full range of colours (PC)

IMPORTANT! In case of large orders

- cable tray with perforated side profile
- cable tray from 2 up to 12m long
- cable tray: 1,2 and 2,5mm thick sheet.

Cable Tray adapted for installation of Cable Clamps: UKZ1, UKZ2

Versions:

Sheet thickness: 1,5 mm

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
KSP200H300/3N	3000	200	220020	2	5,81	16
KSP200H100/6N	6000	200	220021	2	5,81	16
KSP300H100/3N	3000	300	220030	2	6,71	24
KSP300H100/6N	6000	300	220031	2	6,71	24
KSP400H100/3N	3000	400	220040	2	7,61	32
KSP400H100/6N	6000	400	220041	2	7,61	32
KSP500H100/3N	3000	500	220050	2	8,51	41
KSP500H100/6N	6000	500	220051	2	8,51	41
KSP600H100/3N	3000	600	220060	2	9,41	49
KSP600H100/6N	6000	600	220061	2	9,41	49

Connected products:



KKSC...H100N 90°
Horizontal Bend



KKSMC...H100N 45°
Horizontal Bend



TKSC...H100N
Horizontal Tee



CZKSC...H100N
Horizontal Cross-over



LWKSC...H100N 90°
Vertical Bend -
Internal



LZKSC...H100N 90°
Vertical Bend -
External