LZZC...H50 90° Vertical Bend - External

Overview:

APPLICATION
Diversion in cable routing

Material
Hot-dip galv. steel to PN-EN ISO 1461:2011 (HDG)

Available to order:
E- stainless steel (SS)
L- powder coating in a full range of colours (PC)

For joining fittings to cable tray lengths use Straight Connectors LZC...



Versions:

Sheet thickness: **2,0 mm**

Symbol	Width a [mm]	Catalogue number	Quantity in box	Weight 1 pc.
LZZC50H50	**50**	**351505**	**20**	**1,40**
LZZC100H50	**100**	**351510**	**10**	**1,60**
LZZC200H50	**200**	**351520**	**10**	**2,26**
LZZC300H50	**300**	**351530**	**4**	**2,94**
LZZC400H50	**400**	**351540**	**2**	**3,61**
LZZC500H50	**500**	**351550**	**2**	**4,29**
LZZC600H50	**600**	**351560**	**2**	**4,96**

Connected products:

KZC...H50 Cable Tray

KZLC...H50 Cable Tray with Integral Connector

LZCH50 Straight Connector

LCC...H50 U-Shaped Connector

LZGCH50 Articulated Connector

KKZC...H50 90° Horizontal Bend

KKZMC...H50 45° Horizontal Bend

TKZC...H50 Horizontal Tee

CZKZC...H50 Horizontal Cross-over

LZZMC...H50 45° Vertical Bend - External

LZWC...H50 90° Vertical Bend - Internal

LZWMC...H50 45° Vertical Bend - Internal

TRZC...H50 Vertical Tee - Lengthwise

RKZC...H50 Straight Reducer

© 2026 STRADER