

KZP...H100 Cable Tray


Overview:

APPLICATION
Cable routing

Material
Hot-dip galv. steel to PN-EN ISO 1461:2011 (HDG)

Available to order:
E- stainless steel (SS)
L- powder coating in a full range of colours (PC)

To join 2 cable tray lengths firmly use either 1 pair of Straight Connector LZCH100 or 1pc of U-Shaped Connector LCC...H100 and 18 sets of Screw SGF M8x14.



Versions:

Sheet thickness: 1,5 mm

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
KZP100H100/3	3000	100	310210	4	3,95	9800
KZP200H100/3	3000	200	310220	2	5,19	19800
KZP300H100/3	3000	300	310230	2	6,42	29800
KZP400H100/3	3000	400	310240	2	7,66	39800
KZP500H100/3	3000	500	310250	2	8,89	49800
KZP600H100/3	3000	600	310260	2	10,13	59800

Connected products:



KZLP...H100 Cable Tray with Integral Connector
 KKZP...H100 90° Horizontal Bend
 KKZMP...H100 45° Horizontal Bend
 TKZP...H100 Horizontal Tee
 CZKZP...H100 Horizontal Cross-over
 LZZP...H100 90° Vertical Bend - External
 LZZMP...H100 45° Vertical Bend - External
 LZWP...H100 90° Vertical Bend - Internal



LZWMP...H100 45° Vertical Bend - Internal
 TRZP...H100 Vertical Tee - Lengthwise
 RKZP...H100 Straight Reducer
 LZCH100 Straight Connector
 LCC...H100 U-Shaped Connector