

KKZC...H100 90° Horizontal Bend

Overview:

APPLICATION

Diversion in cable routing

Material


Hot-dip galv. steel to PN-EN ISO 1461:2011 (HDG)

Available to order:

E- stainless steel (SS)

L- powder coating in a full range of colours (PC)

For joining fittings to cable tray lengths use Straight Connectors LZC...



Versions:

Sheet thickness: **2,0 mm**

Symbol	Width a [mm]	Catalogue number	Quantity in box	Weight 1 pc.
KKZC100H100	100	310710	6	3,17
KKZC200H100	200	310720	6	4,04
KKZC300H100	300	310730	2	5,64
KKZC400H100	400	310740	2	7,49
KKZC500H100	500	310750	2	9,60
KKZC600H100	600	310760	2	11,96

Connected products:



KZWC...H100
Reinforced
Cable Tray



KZLC...H100
Cable Tray with
Integral
Connector



LZCH100
Straight
Connector



LZGCH100
Articulated
Connector



LCC...H100
U-Shaped
Connector



KKZMC...H100
45° Horizontal
Bend



TKZC...H100
Horizontal Tee



CZKZC...H100
Horizontal
Cross-over



LZVC...H100 90°
Vertical Bend -
External



LZVMC...H100
45° Vertical
Bend - External



LZVIC...H100
90° Vertical
Bend - Internal



LZVMC...H100
45° Vertical
Bend - Internal



TRZC...H100
Vertical Tee -
Lengthwise



RKZC...H100
Straight
Reducer