

## KZP...H200 Cable Tray


### Overview:

**APPLICATION**  
Cable routing

**Material**  
Hot-dip galv. steel to PN-EN ISO 1461:2011 (HDG)

**Available to order:**  
E- stainless steel (SS)  
L- powder coating in a full range of colours (PC)

**To join 2 cable tray lengths firmly use either 1 pair of Straight Connector LZCH200 or 1pc of U-Shaped Connector LCC...H200 and 26 sets of Screw SGF M8×14.**



### Versions:

Sheet thickness: 1,5 mm

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
KZP200H200/3	3000	200	370220	2	7,66	39800
KZP300H200/3	3000	300	370230	2	8,89	59800
KZP400H200/3	3000	400	370240	2	10,13	79800
KZP500H200/3	3000	500	370250	2	11,37	99800
KZP600H200/3	3000	600	370260	2	12,60	119800

### Connected products:



KZLP...H200 Cable Tray with Integral Connector   
 KKZP...H200 90° Horizontal Bend   
 KKZMP...H200 45° Horizontal Bend   
 TKZP...H200 Horizontal Tee   
 CZKZP...H200 Horizontal Cross-over   
 LZZP...H200 90° Vertical Bend - External   
 LZZMP...H200 45° Vertical Bend - External   
 LZWP...H200 90° Vertical Bend - Internal



LZWMP...H200 45° Vertical Bend - Internal   
 TRZP...H200 Vertical Tee - Lengthwise   
 RKZP...H200 Straight Reducer   
 LZCH200 Straight Connector   
 LCC...H200 U-Shaped Connector