


## DUD...H45N Cable Ladder

### Overview:

**Application**  
Cable routing

**Material**  
Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

**Available to order:**  
**F-** steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)  
**E-** stainless steel sections to 3m long (SS)  
**L-** powder coating in a full range of colours (PC)



**NOTE: Cable ladder with rungs adapted for use with Cable Clamps UK**

**Available upon special order:**

- cable ladders 2m long
- cable ladders 150, 250mm wide
- production capability of perforated rungs

### Versions:

Sheet thickness: **1,2 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
DUD100H45/3N	3000	100	446010	4	1,71	2700
DUD100H45/6N	6000	100	446110	2	1,71	2700
DUD200H45/3N	3000	200	446020	4	1,94	5400
DUD200H45/6N	6000	200	446120	2	1,94	5400
DUD300H45/3N	3000	300	446030	4	2,17	8100
DUD300H45/6N	6000	300	446130	2	2,17	8100
DUD400H45/3N	3000	400	446040	2	2,51	10800
DUD400H45/6N	6000	400	446140	2	2,51	10800
DUD500H45/3N	3000	500	446050	2	2,62	13500
DUD500H45/6N	6000	500	446150	2	2,62	13500
DUD600H45/3N	3000	600	446060	2	2,85	16200
DUD600H45/6N	6000	600	446160	2	2,85	16200

### Connected products:

