


DUC...H45N Cable Ladder

Overview:

Application
Cable routing

Material
Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:
F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)
E- stainless steel sections to 3m long (SS)
L- powder coating in a full range of colours (PC)



NOTE: Cable ladder with rungs adapted for use with Cable Clamps UK
Available upon special order:
- cable ladders 2m long
- cable ladders 150, 250mm wide
- production capability of perforated rungs

Versions:

Sheet thickness: **2,0 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
DUC100H45/3N	3000	100	446610	4	2,74	2700
DUC100H45/6N	6000	100	446710	2	2,74	2700
DUC200H45/3N	3000	200	446620	4	3,10	5400
DUC200H45/6N	6000	200	446720	2	3,10	5400
DUC300H45/3N	3000	300	446630	4	3,48	8100
DUC300H45/6N	6000	300	446730	2	3,48	8100
DUC400H45/3N	3000	400	446640	2	4,02	10800
DUC400H45/6N	6000	400	446740	2	4,02	10800
DUC500H45/3N	3000	500	446650	2	4,20	13500
DUC500H45/6N	6000	500	446750	2	4,20	13500
DUC600H45/3N	3000	600	446660	2	4,57	16200
DUC600H45/6N	6000	600	446760	2	4,57	16200

Connected products:



LDC...H45N 90° Horizontal Bend