


## DKP...H50N Cable Ladder

### Overview:

**Application**  
Cable routing

**Material**  
Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

**Available to order:**  
**F-** steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)  
**E-** stainless steel sections to 3m long (SS)  
**L-** powder coating in a full range of colours (PC)



**NOTE: Cable ladder with rungs adapted for use with Cable Clamps UKZ**

**Available upon special order:**

- cable ladders 2m long
- cable ladders 150, 250mm wide.

### Versions:

Sheet thickness: 1,5 mm

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
DKP100H50/3N	3000	100	455410	4	2,18	3200
DKP200H50/3N	3000	200	455420	4	2,45	6400
DKP300H50/3N	3000	300	455430	4	2,73	9600
DKP400H50/3N	3000	400	455440	2	3,14	12800
DKP500H50/3N	3000	500	455450	2	3,27	16000
DKP600H50/3N	3000	600	455460	2	3,55	19200

### Connected products:



LDDCH50N Articulated Connector - Attachable



LDC...H50N 90° Horizontal Bend



UKZ1/UKZ01... Cable Clamp