


DKD...H60N Cable Ladder

Overview:

Application
Cable routing

Material
Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:
F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)
E- stainless steel sections to 3m long (SS)
L- powder coating in a full range of colours (PC)



NOTE: Cable ladder with rungs adapted for use with Cable Clamps UKZ

Available upon special order:

- cable ladders 2m long
- cable ladders 150, 250mm wide.

Versions:

Sheet thickness: 1,2 mm

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
DKD100H60/3N	3000	100	465110	4	2,01	4200
DKD100H60/6N	6000	100	465210	2	2,01	4200
DKD200H60/3N	3000	200	465120	4	2,24	8400
DKD200H60/6N	6000	200	465220	2	2,24	8400
DKD300H60/3N	3000	300	465130	2	2,47	12600
DKD300H60/6N	6000	300	465230	2	2,47	12600
DKD400H60/3N	3000	400	465140	2	2,81	16800
DKD400H60/6N	6000	400	465240	2	2,81	16800
DKD500H60/3N	3000	500	465150	2	2,92	21000
DKD500H60/6N	6000	500	465250	2	2,92	21000
DKD600H60/3N	3000	600	465160	2	3,15	25200
DKD600H60/6N	6000	600	465260	2	3,15	25200

Connected products:

