


DKP...H60N Cable Ladder

Overview:

Application
Cable routing

Material
Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:
F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)
E- stainless steel sections to 3m long (SS)
L- powder coating in a full range of colours (PC)



NOTE: Cable ladder with rungs adapted for use with Cable Clamps UKZ

Available upon special order:

- cable ladders 2m long
- cable ladders 150, 250mm wide.

Versions:

Sheet thickness: 1,5 mm

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
DKP100H60/3N	3000	100	465410	4	2,42	4200
DKP100H60/6N	6000	100	465510	2	2,42	4200
DKP200H60/3N	3000	200	465420	4	2,69	8400
DKP200H60/6N	6000	200	465520	2	2,69	8400
DKP300H60/3N	3000	300	465430	2	2,97	12600
DKP300H60/6N	6000	300	465530	2	2,97	12600
DKP400H60/3N	3000	400	465440	2	3,38	16800
DKP400H60/6N	6000	400	465540	2	3,38	16800
DKP500H60/3N	3000	500	465450	2	3,51	21000
DKP500H60/6N	6000	500	465550	2	3,51	21000
DKP600H60/3N	3000	600	465460	2	3,79	25200
DKP600H60/6N	6000	600	465560	2	3,79	25200

Connected products:

							
LDC/LDOCH60 Straight Connector	LKDC/LKDOCH60 0 Angle Connector	LDDCH60N Articulated Connector - Attachable	LGC/LGOCH60 Articulated Connector	LDP/LDOP...H60 90° Horizontal Bend	LDZP...H60N 90° Horizontal Bend - External	TDP/TDOP...H60 Horizontal Tee	CZDP/CZDOP...H 60 Horizontal Cross-over
							
LPDW...H60 90° Vertical Bend - Internal	LPDZP/LPDZOP... .H60 90° Vertical Bend - External	LPDP...H60N Adjustable Vertical Bend	RDSP...H60N Straight Reducer	RDL...H60N Left Reducer	RDPP...H60N Right Reducer	UKZ1/UKZO1... Cable Clamp	