


## DKP...H80N Cable Ladder

### Overview:

**Application**  
Cable routing

**Material**  
Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

**Available to order:**  
**F-** steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)  
**E-** stainless steel sections to 3m long (SS)  
**L-** powder coating in a full range of colours (PC)



**NOTE: Cable ladder with rungs adapted for use with Cable Clamps UKZ**

**Available upon special order:**

- cable ladders 2m long
- cable ladders 150, 250mm wide.

### Versions:

Sheet thickness: 1,5 mm

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
DKP100H80/3N	3000	100	495110	2	2,90	6200
DKP200H80/3N	3000	200	495120	2	3,17	12400
DKP300H80/3N	3000	300	495130	2	3,45	18600
DKP400H80/3N	3000	400	495140	2	3,86	24800
DKP500H80/3N	3000	500	495150	2	3,99	31000
DKP600H80/3N	3000	600	495160	2	4,27	37200

### Connected products:

NO80N Protective Cap (Set)	LDCH80N Straight Connector	LKDCH80N Angle Connector	LDDCH80N Articulated Connector - Attachable	LGCH80N Articulated Connector	LDP...H80N 90° Horizontal Bend	LDZP...H80N 90° Horizontal Bend - External	TDP...H80N Horizontal Tee
CZDP...H80N Horizontal Cross-over	LPDWP...H80N 90° Vertical Bend - Internal	LPDZP...H80N 90° Vertical Bend - External	LPDP...H80N Adjustable Vertical Bend	RDSP...H80N Straight Reducer	RDLP...H80N Left Reducer	RDPP...H80N Right Reducer	UKZ1/UKZO1... Cable Clamp