

MO-60÷360 Stožár hromosvodu

Informace:

POUŽITIE

Ochrana objektov proti úderom blesku.

MATERIÁL

Oveľový plech žiarovo zinkovaný ponorom.

Ostatné parametre stožiaru v katalógovom liste.



Verze:

Symbol	Kat. číslo	Hmotnosť [kg]	H [m]	S [m ²]	Mf [kNm]	n x Øs/ØM	a x a x h [m]	Trn stožáru	HI [m]
MO-60 EN 40-5: 2004	11050001 43	40,00	6	3,20	14,00	4xM18/200	F-100/30	S-40	2
MO-80 195/60 EN 40-5: 2004	11050003 86	80,00	8	4,00	16,00	4xM24/300	F-100/43	S-60	2
MO-120 182/90 EN 40-5: 2004	11050003 82	90,00	12	4,40	18,00	4xM24/300	F150/43	S-100	2
MO-170	11050001 70	140,00	17	6,80	25,00	4xM24/250	F160	M-100SE	8
MO-220 310/90 EN 1090-2	11050001 27	435,00	22	14,00	85,00	4xM33/400	1,6x1,6x1,8	2x-S-83	6
MO-240 340/90 EN 1090-2	11050001 46	532,00	24	18,00	97,00	4xM33/440	1,6x1,6x1,8	2x-S-93	6
MO-260	11050002 52	680,00	26	19,00	120,00	8xM24/550	1,6x1,6x1,8	M-200	6
MO-280	11050002 80	735,00	28	20,00	150,00	8xM24/550	1,6x1,6x1,8	M-220	10
MO-360	11050003 60	1180,00	36	32,00	220,00	12xM30/600	1,7x1,7x2,0	H27,5	8.5