

GDA1/2...- 4-5P Protipožiarná bariéra (63-2500 A)

Informace:

Použitie

Služi na bezpečnostné oddelenie rovných dielov alebo kolien proti prenikaniu plameňov.

- verzie pre 63 až 2500 A.
- stupeň ochrany REI 120 (2h).



A	GDA 4		GDA 5	
	Symbol/Code	Symbol/Code	Symbol/Code	Symbol/Code
63/100/150	GDA101006M	GDA101006	GDA201006M	GDA201006
250/400	GDA104006	GDA104006	GDA204006	GDA204006
500/800/1000	GDA108006	GDA108006	GDA208006	GDA208006
1250	GDA116006	GDA116006	GDA216006	GDA216006
1250/1600	GDA125006	GDA125006	GDA225006	GDA225006
2000/2500	GDA125006	GDA125006	GDA225006	GDA225006

Materiál

- Protipožiarňý materiál je vo vnútri prípojnice v mieste prechodu medzi poschodiami alebo miestnosťami.

Verze:

Symbol	Pól	El. prúd [A]
GDA101006M	4P	63
GDA201006M	5P	63
GDA104006	4P	250
GDA204006	5P	250
GDA108006	4P	500
GDA208006	5P	500
GDA110006	4P	1000
GDA210006	5P	1000
GDA116006	4P	1250
GDA216006	5P	1250
GDA125006	4P	2000
GDA225006	5P	2000