

LKJH42 Angle Connector

Overview:

Application

Connecting cable routes.

Material


Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:

F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)

E- stainless steel (SS)

L- powder coating in a full range of colours (PC)



Use 4 Screw Sets SGK M6×10 or SG M6×10 to install
Optional bending or break-off of any required length

Versions:

Sheet thickness: **1,0 mm**

Symbol	Length L [m]	Catalogue number	Quantity in box	Height H [mm]	Weight 1 pc.
LKJH42	140	142200	100	35	0,02
LKJH42/1	1000	142600	100	35	0,15

Connected products:



KAJ...H42 Cable Tray



KGL...H42 Cable Tray



KGJ...H42 Cable Tray



KGR...H42 Cable Tray



KCJ...H42 Cable Tray



KCL...H42 Cable Tray



KOL...H42 Cable Tray



KOJ...H42 Cable Tray



KBR...H42 Cable Tray



KBL...H42 Cable Tray



KBJ...H42 Cable Tray



OPZJ...H42 Horizontal Bypass



OPZBJ...H42 Horizontal Bypass



OPNJ...H42 Vertical Bypass



OPNBj...H42 Vertical Bypass



LUJ...H42 90° Vertical Bend



LUBj...H42 90° Vertical Bend



LUMJ...H42 45° Vertical Bend



LUMBj...H42 45° Vertical Bend



LUPJ...H42 90° Vertical Bend



LUMPJ...H42 45° Vertical Bend



TRSJ...H42 Vertical Tee - Crosswise



TRSBj...H42 Vertical Tee - Crosswise



SG... Screw Set



SM... Screw Set