

KKNMt 45° Horizontal Bend 3 Comp.

Overview:

Application

Diversion in cable routing


Material

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:

F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)

E- stainless steel (SS)




Versions:


Sheet thickness: **1,0 mm**

Symbol	Width a [mm]	Catalogue number	Quantity in box	Weight 1 pc.
KKNMt175H28	175	521217	4	0,66
KKNMt190H28	190	521219	4	0,76
KKNMt240H28	240	521224	4	0,96
KKNMt340H28	340	521234	4	1,48


Connected products:



KN Underfloor Trunking



KNd Underfloor Trunking 2 Comp.



KNT Underfloor Trunking 3 Comp.




KKN 90° Horizontal Bend



KKNd 90° Horizontal Bend 2 Comp.



KKNt 90° Horizontal Bend 3 Comp.



KKNM 45° Horizontal Bend



KKNMd 45° Horizontal Bend 2 Comp.



TKN Horizontal Tee



CZKN Horizontal Cross-over



LK Vertical Bend



LKd Vertical Bend 2 Comp.



LKt Vertical Bend 3 Comp.



RKN Straight Reducer



RKNd Straight Reducer 2 Comp.



RKNt Straight Reducer 3 Comp.