

LKt Vertical Bend 3 Comp.

Overview:

Application

Diversion in cable routing from the horizontal to the vertical plane

Material


Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:

F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)

E- stainless steel (SS)

Cover included




Versions:


Sheet thickness: **1,0 mm**

Symbol	Width a [mm]	Catalogue number	Quantity in box	Weight 1 pc.
LKt175H28	175	521717	4	0,78
LKt190H28	190	521719	4	0,82
LKt240H28	240	521724	4	0,96
LKt340H28	340	521734	4	1,22


Connected products:



KN Underfloor Trunking



KNd Underfloor Trunking 2 Comp.



KNT Underfloor Trunking 3 Comp.



KKN 90° Horizontal Bend



KKNd 90° Horizontal Bend 2 Comp.



KKNt 90° Horizontal Bend 3 Comp.



KKNM 45° Horizontal Bend



KKNMd 45° Horizontal Bend 2 Comp.



KKNMt 45° Horizontal Bend 3 Comp.



TKN Horizontal Tee



CZKN Horizontal Cross-over



LK Vertical Bend



LKd Vertical Bend 2 Comp.



RKN Straight Reducer



RKNd Straight Reducer 2 Comp.



RKNt Straight Reducer 3 Comp.