

KKNMt 45° Horizontal Bend 3 Comp.

Overview:

Application

Diversion in cable routing



Material

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:

F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)

E- stainless steel (SS)




Versions:


Sheet thickness: **1,0 mm**

Symbol	Width a [mm]	Catalogue number	Quantity in box	Weight 1 pc.
KKNMt 175H48	175	541217	4	0,88
KKNMt 190H48	190	541219	4	0,97
KKNMt 240H48	240	541224	4	1,18
KKNMt 340H48	340	541234	4	1,77


Connected products:



KN Underfloor Trunking



KNd Underfloor Trunking 2 Comp.



KNt Underfloor Trunking 3 Comp.




KKN 90° Horizontal Bend



KKNd 90° Horizontal Bend 2 Comp.



KKNt 90° Horizontal Bend 3 Comp.




KKNM 45° Horizontal Bend



KKNMd 45° Horizontal Bend 2 Comp.



TKN Horizontal Tee



CZKN Horizontal Cross-over



LK Vertical Bend



LKd Vertical Bend 2 Comp.



LKt Vertical Bend 3 Comp.



RKN Straight Reducer



RKNd Straight Reducer 2 Comp.



RKNt Straight Reducer 3 Comp.