

OPZBJ...H42 Horizontal Bypass

Overview:

Application

Bypassing mechanical obstacles in cable routing

Material


Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:

F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)

E- stainless steel (SS)

L- powder coating in a full range of colours (PC)



For installation use Screw Sets SGK M6×10 or SG M6×10 and Straight Connectors LPL or LPP. Quick and convenient installation by the use of dismantled parts. This innovative solution allows for fast and safe cable laying without the need of pulling

Versions:

Sheet thickness: **1,0 mm**

Symbol	Width a [mm]	Catalogue number	Quantity in box	Weight 1 pc.
OPZBJ50H42	50	143301	2	0,50
OPZBJ100H42	100	143501	2	0,77
OPZBJ150H42	150	143701	2	1,03
OPZBJ200H42	200	143801	2	1,29
OPZBJ300H42	300	144001	2	1,83
OPZBJ400H42	400	148301	2	2,10
OPZBJ500H42	500	148401	2	2,52
OPZBJ600H42	600	148501	2	3,02

Connected products:



KAJ...H42 Cable Tray KGL...H42 Cable Tray KGJ...H42 Cable Tray KGR...H42 Cable Tray KCJ...H42 Cable Tray KCL...H42 Cable Tray KOL...H42 Cable Tray KOJ...H42 Cable Tray



KBR...H42 Cable Tray KBJ...H42 Cable Tray SG... Screw Set SM... Screw Set