

CD40H20... Channel

Overview:

Application

Used for suspending lighting, and as construction element for installing cable trays, and ladders. Used as an element for supporting Brackets WS, WZS, WSZ, WWT, WPT, WWC, WPL, WTL, WW, WWS, WWD, WMC, WMCN, WWCN, and WWC.

Material

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)


Available to order:

F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)

E- stainless steel sections to 3m long (SS)

L- powder coating in a full range of colours (PC)

Important! In case of large quantity orders available are any sections to 6m long. For the assembly of channel in combination with channel connector use Screw Sets SGK M10x20 or SG M10x20



Versions:

Sheet thickness: **1,2 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Height H [mm]	Weight 1 pc.
CD40H20/2	2000	40	611620	8	20	1,46
CD40H20/3	3000	40	611630	8	20	2,19

Connected products:

							
CWZJ30H20... Support Channel	PCWZJ... Cover For Channel	PTJ... Perforated Steel Band	PZC... Assembly Plate	NO40x20 Protective Cap	NO40x47 Protective Cap	NOK... Protective Cap	NO80x37 Protective Cap
							
SZB35H7... DIN Rail	SZB35H15... DIN Rail	TSO... Galvanised Steel Tape	DSO... Galvanised Steel Wire	SZP35H7... DIN Rail	SZP35H15... DIN Rail	LCW20H10 Channel Connector	NO30x30 Protective Cap
							
NO40x40N Protective Cap	NO40x60 Protective Cap	DPH... I-Beam	NO40x30 Protective Cap	NO50x30 Protective Cap			