

OPNJ...H42 Vertical Bypass

Overview:

Application

Bypassing mechanical obstacles in cable routing

Material


Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:

F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)

E- stainless steel (SS)

L- powder coating in a full range of colours (PC)



For installation use Screw Sets SGK M6×10 or SG M6×10 and Straight Connectors LPL or LPP. Quick and convenient installation by the use of dismantled parts. This innovative solution allows for fast and safe cable laying without the need of pulling

Versions:

Sheet thickness: **1,0 mm**

Symbol	Width a [mm]	Catalogue number	Quantity in box	Weight 1 pc.
OPNJ50H42	50	147205	2	0,50
OPNJ100H42	100	147210	2	0,77
OPNJ150H42	150	147215	2	1,03
OPNJ200H42	200	147220	2	1,29
OPNJ300H42	300	147230	2	1,83
OPNJ400H42	400	147240	2	2,10
OPNJ500H42	500	147250	2	2,52
OPNJ600H42	600	147260	2	3,02

Connected products:



KAJ...H42 Cable Tray KGL...H42 Cable Tray KGJ...H42 Cable Tray KGR...H42 Cable Tray KCJ...H42 Cable Tray KCL...H42 Cable Tray KOL...H42 Cable Tray KOJ...H42 Cable Tray



KBR...H42 Cable Tray KBJ...H42 Cable Tray SG... Screw Set SM... Screw Set