


DUP...H120N Cable Ladder

Overview:

Application
Cable routing

Material
Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:
F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)
E- stainless steel sections to 3m long (SS)
L- powder coating in a full range of colours (PC)



NOTE: Cable ladder with rungs adapted for use with Cable Clamps UK

Available upon special order:

- cable ladders 2m long
- cable ladders 150, 250mm wide
- production capability of perforated rungs

Versions:

Sheet thickness: **1,5 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
DUP100H120/3N	3000	100	473010	2	3,86	8400
DUP100H120/6N	6000	100	473110	2	3,86	8400
DUP200H120/3N	3000	200	473020	2	4,11	18400
DUP200H120/6N	6000	200	473120	2	4,11	18400
DUP300H120/3N	3000	300	473030	2	4,41	28600
DUP300H120/6N	6000	300	473130	2	4,41	28600
DUP400H120/3N	3000	400	473040	2	4,82	38800
DUP400H120/6N	6000	400	473140	2	4,82	38800
DUP500H120/3N	3000	500	473050	2	4,96	49000
DUP500H120/6N	6000	500	473150	2	4,96	49000
DUP600H120/3N	3000	600	473060	2	5,23	59200
DUP600H120/6N	6000	600	473160	2	5,23	59200