


## DGOD...H60N Cable Ladder

### Overview:

**APPLICATION**  
Cable routing

**MATERIAL**  
Steel, strip-galv. acc. to the  
Sendzimir method PN-EN 10346:2011  
Available finishes:  
L- powder coating in a full range of colours (PC)



- For assembly use 2 pcs of Straight connectors LDC/LDOCH60 and 8 sets of screw SGKM8x14
- For vertical direction change use 2 pcs of Articulated Connector LGC/LGOCH60 and 8 sets of screw SGKM8x14
- For horizontal direction change use 2 pcs of Angle Connector LKD/LKDOCH60 and 8 sets of screw SGKM8x14






















**Max. safe load: 20 kg/m**  
**Max. spacing of supports: 1.5m**

### Versions:

Sheet thickness: **1,2 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]
DGOD100H60/3N	3000	100	867010	2	2,01
DGOD100H60/6N	6000	100	867110	2	2,01
DGOD200H60/3N	3000	200	867020	2	2,24
DGOD200H60/6N	6000	200	867120	2	2,24
DGOD300H60/3N	3000	300	867030	2	2,47
DGOD300H60/6N	6000	300	867130	2	2,47
DGOD400H60/3N	3000	400	867040	2	2,81
DGOD400H60/6N	6000	400	867140	2	2,81

### Connected products:

 LDP/LDOP...H60 90° Horizontal Bend	 LDOPE 90° ladder bend	 TDP/TDOP...H60 Horizontal Tee	 CZDP/CZDOP...60 Horizontal Cross-over	 HCZDP/CZDOPE Horizontal Cross-over	 LPDWOP...H60N 90° Vertical Bend - Internal	 LPDZOPN 90° Vertical Bend - External	 LDC/LDOCH60 Straight Connector
 LDOCH60E Ladder coupler	 LGC/LGOCH60 Articulated Connector	 LKDOCH60N Angle Connector	 LKDOCH60E Angle Connector	 ZM/ZMO Hold Down Clamp	 ZMOE Hold Down Clamp	 RO1... Cable Protection Piece Clamp	 UKO1E Cable Clamp
 SGN Screw Set	 SM... Screw Set	 NS... Nut	 PP... Washer	 PW... Washer			