


## KBJ...H110 Cable Tray

### Overview:

**Application**  
Cable routing

**Material**  
Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

**Available to order:**  
F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)  
E- stainless steel (SS)  
L- powder coating in a full range of colours (PC)



**Important!**  
**Possibility of joining cable tray KBR..., KBL..., KBJ... and KBD... sections together through sliding one into another and connector-free assembly. Cable Tray sections of KBJ... can be joined up only through the use of connectors (lack of cut in the flange at the end of side profile). Available when ordering in large quantity are 6m long tray sections. To install cable tray use Screw Sets SGK M6x12 or SG M6x12.**

### Versions:

Sheet thickness: 1,0 mm

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
KBJ100H110/3	3000	100	121610	4	2,80	10800
KBJ100H110/6	6000	100	121611	4	2,80	10800
KBJ150H110/3	3000	150	121615	4	3,20	16300
KBJ150H110/6	6000	150	121616	4	3,20	16300
KBJ200H110/3	3000	200	121620	4	3,60	21800
KBJ200H110/6	6000	200	121621	4	3,60	21800
KBJ300H110/3	3000	300	121630	2	4,60	32800
KBJ300H110/6	6000	300	121631	2	4,60	32800
KBJ400H110/3	3000	400	121640	2	5,20	43800
KBJ400H110/6	6000	400	121641	2	5,20	43800
KBJ500H110/3	3000	500	121650	2	6,10	54800
KBJ500H110/6	6000	500	121651	2	6,10	54800
KBJ600H110/3	3000	600	121660	2	6,80	65800
KBJ600H110/6	6000	600	121661	2	6,80	65800