


## KBD...H110 Cable Tray

### Overview:

**Application**  
 Cable routing

**Material**  
 Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

**Available to order:**  
**F-** steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)  
**E-** stainless steel (SS)  
**L-** powder coating in a full range of colours (PC)



**Important!**  
 Possibility of joining cable tray KBR..., KBL..., KBJ... and KBD... sections together through sliding one into another and connector-free assembly. Cable Tray sections of KBP... can be joined up only through the use of connectors (lack of cut in the flange at the end of side profile). Available when ordering in large quantity are 6m long tray sections.  
 To install cable tray use Screw Sets SGK M6x12 or SG M6x12.

### Versions:

Sheet thickness: **1,2 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
KBD100H110/3	3000	100	121810	4	3,59	10800
KBD150H110/3	3000	150	121815	4	3,99	16300
KBD200H110/3	3000	200	121820	4	4,49	21800
KBD300H110/3	3000	300	121830	2	5,49	32800
KBD400H110/3	3000	400	121840	2	6,49	43800
KBD500H110/3	3000	500	121850	2	7,49	54800
KBD600H110/3	3000	600	121860	2	8,49	65800