

KBP...H110 Cable Tray

Overview:

Application
Cable routing

Material


Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:

F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)

E- stainless steel (SS)

L- powder coating in a full range of colours (PC)



Important!

Possibility of joining cable tray KBR..., KBL..., KBJ... and KBD... sections together through sliding one into another and connector-free assembly. Cable Tray sections of KBP... can be joined up only through the use of connectors (lack of cut in the flange at the end of side profile).

Available when ordering in large quantity are 6m long tray sections.

To install cable tray use Screw Sets SGK M6x12 or SG M6x12.

Versions:

Sheet thickness: 1,5 mm

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
KBP100H110/3	3000	100	122010	4	4,10	10800
KBP100H110/6	6000	100	122011	4	4,10	10800
KBP150H110/3	3000	150	122015	4	4,70	16300
KBP150H110/6	6000	150	122016	4	4,70	16300
KBP200H110/3	3000	200	122020	2	5,30	21800
KBP200H110/6	6000	200	122021	2	5,30	21800
KBP300H110/3	3000	300	122030	2	6,50	32800
KBP300H110/6	6000	300	122031	2	6,50	32800
KBP400H110/3	3000	400	122040	2	7,70	43800
KBP400H110/6	6000	400	122041	2	7,70	43800
KBP500H110/3	3000	500	122050	2	9,00	54800
KBP500H110/6	6000	500	122051	2	9,00	54800
KBP600H110/3	3000	600	122060	2	10,20	65800
KBP600H110/6	6000	600	122061	2	10,20	65800