

## KKPJ...H110 90° Horizontal Bend

### Overview:

#### Application

Diversions in cable routing.

#### Material



Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

#### Available to order:

**F**- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)

**E**- stainless steel (SS)

**L**- powder coating in a full range of colours (PC)



For installation use Screw Sets SGK M6×12 or SG M6×12.

In case of special orders please specify dimensions a and b.

### Versions:

Sheet thickness: **1,0 mm**

| Symbol      | Width a [mm] | Catalogue number | Quantity in box | Weight 1 pc. |
|-------------|--------------|------------------|-----------------|--------------|
| KKPJ100H110 | 100          | 120114           | 10              | 0,82         |
| KKPJ150H110 | 150          | 120214           | 10              | 1,06         |
| KKPJ200H110 | 200          | 120314           | 10              | 1,33         |
| KKPJ300H110 | 300          | 120414           | 4               | 1,97         |
| KKPJ400H110 | 400          | 120514           | 4               | 2,66         |
| KKPJ500H110 | 500          | 120614           | 2               | 3,62         |
| KKPJ600H110 | 600          | 120714           | 2               | 4,63         |