

WTRE... Bracket

Overview:

Application

Supporting cable trays and ladders, pipes, and other systems' components under very heavy load


Material

Hot-dip galv. steel to PN-EN ISO 1461:2011 (HDG)

Available to order:

E- stainless steel (SS)

L- powder coating in a full range of colours (PC)



Versions:

Symbol	Length L [m]	Catalogue number	Quantity in box	Height H [mm]	Weight 1 pc.	Maximum load Fmax[kN]
WTRE200	215	713220	10	200	1,90	8,00
WTRE300	315	713320	8	200	2,70	7,00
WTRE400	415	713420	6	220	3,40	7,00
WTRE500	515	713520	1	220	4,30	6,00
WTRE600	615	713620	1	220	5,20	6,00
WTRE700	715	713720	1	220	5,80	5,50
WTRE800	815	713820	1	280	6,30	7,00
WTRE900	915	713920	1	280	6,90	7,00
WTRE1000	1015	713120	1	280	7,50	6,50
WTRE1100	1115	713121	1	280	8,10	6,00
WTRE1200	1215	713122	1	280	8,70	5,00
WTRE1300	1315	713123	1	280	9,40	4,50
WTRE1400	1415	713124	1	280	10,10	4,00
WTRE1500	1515	713125	1	280	10,70	3,50