

KAJ...H60 Cable Tray

Overview:

Application
Cable routing

Material

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:

F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)

E- stainless steel (SS)

L- powder coating in a full range of colours (PC)



Important! Joining cable tray sections together only through the use of connectors (lack of cut in the flange at the end of side profile). To install cable tray use Screw Sets SGK M6x12 or SG M6x12.

Benefits of the New System:

- large perforation in the tray side: of size 24 × 65mm, and in the bottom, sized 34 × 65mm, allow cable bundles to be pulled out from anywhere within the tray without the need to use any fittings
- dense perforation for excellent heat transfer, designed to enable cable tray installation on supports from BAKS anywhere within the system
- rounded tray flange edges with longitudinal ribbing allow the covers to snap firmly into place

Versions:

Sheet thickness: **1,0 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
KAJ50H60/3	3000	50	170716	12	1,33	2900
KAJ100H60/3	3000	100	170816	12	1,58	5800
KAJ150H60/3	3000	150	170916	6	1,92	8800
KAJ200H60/3	3000	200	171016	6	2,21	11800
KAJ300H60/3	3000	300	171116	6	2,87	17800
KAJ400H60/3	3000	400	171216	4	3,54	23800
KAJ500H60/3	3000	500	171316	2	4,19	29800
KAJ600H60/3	3000	600	171416	2	4,84	35800