

KAP...H60 Cable Tray

Overview:

Application
 Cable routing

Material
 Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:
F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)
E- stainless steel (SS)
L- powder coating in a full range of colours (PC)



Important! Joining cable tray sections together only through the use of connectors (lack of cut in the flange at the end of side profile).
To install cable tray use Screw Sets SGK M6x12 or SG M6x12.

Benefits of the New System:
 - large perforation in the tray side: of size 24 × 65mm, and in the bottom, sized 34 × 65mm, allow cable bundles to be pulled out from anywhere within the tray without the need to use any fittings
 - dense perforation for excellent heat transfer, designed to enable cable tray installation on supports from BAKS anywhere within the system
 - rounded tray flange edges with longitudinal ribbing allow the covers to snap firmly into place

Versions:

Sheet thickness: 1,5 mm

| Symbol | Length L [m] | Width a [mm] | Catalogue number | Quantity in box | Weight [1m] | Effective section |
|-------------|--------------|--------------|------------------|-----------------|-------------|-------------------|
| KAP50H60/3 | 3000 | 50 | 171515 | 12 | 2,09 | 2900 |
| KAP100H60/3 | 3000 | 100 | 171516 | 12 | 2,37 | 5800 |
| KAP150H60/3 | 3000 | 150 | 171616 | 6 | 2,88 | 8800 |
| KAP200H60/3 | 3000 | 200 | 171716 | 6 | 3,32 | 11800 |
| KAP300H60/3 | 3000 | 300 | 171816 | 6 | 4,31 | 17800 |
| KAP400H60/3 | 3000 | 400 | 171916 | 4 | 5,31 | 23800 |
| KAP500H60/3 | 3000 | 500 | 172016 | 2 | 6,29 | 29800 |
| KAP600H60/3 | 3000 | 600 | 172116 | 2 | 7,26 | 35800 |