



## KSC...H100N Cable Tray

### Overview:

#### Application

Cable routing in halls or on-site with limited number of supporting structures. High tray durability allows for applying spacing of supports even every 6m.



#### Material

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

#### Available to order:

**F**- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)  
**E**- stainless steel (SS)  
**L**- powder coating in a full range of colours (PC)

#### IMPORTANT! In case of large orders

- cable tray with perforated side profile
- cable tray from 2 up to 12m long
- cable tray: 1,2 and 2,5mm thick sheet.

Cable Tray adapted for installation of Cable Clamps: UKZ1, UKZ2

### Versions:

Sheet thickness: **2,0 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
<b>KSC200H100/3N</b>	<b>3000</b>	<b>200</b>	<b>220120</b>	<b>2</b>	<b>7,24</b>	<b>16</b>
<b>KSC200H100/6N</b>	<b>6000</b>	<b>200</b>	<b>220121</b>	<b>2</b>	<b>7,24</b>	<b>16</b>
<b>KSC300H100/3N</b>	<b>3000</b>	<b>300</b>	<b>220130</b>	<b>2</b>	<b>8,14</b>	<b>24</b>
<b>KSC300H100/6N</b>	<b>6000</b>	<b>300</b>	<b>220131</b>	<b>2</b>	<b>8,14</b>	<b>24</b>
<b>KSC400H100/3N</b>	<b>3000</b>	<b>400</b>	<b>220140</b>	<b>2</b>	<b>9,04</b>	<b>32</b>
<b>KSC400H100/6N</b>	<b>6000</b>	<b>400</b>	<b>220141</b>	<b>2</b>	<b>9,04</b>	<b>32</b>
<b>KSC500H100/3N</b>	<b>3000</b>	<b>500</b>	<b>220150</b>	<b>2</b>	<b>9,94</b>	<b>41</b>
<b>KSC500H100/6N</b>	<b>6000</b>	<b>500</b>	<b>220151</b>	<b>2</b>	<b>9,94</b>	<b>41</b>
<b>KSC600H100/3N</b>	<b>3000</b>	<b>600</b>	<b>220160</b>	<b>2</b>	<b>10,84</b>	<b>49</b>
<b>KSC600H100/6N</b>	<b>6000</b>	<b>600</b>	<b>220161</b>	<b>2</b>	<b>10,84</b>	<b>49</b>