

## OPZNJ...H30 Horizontal Bypass

### Overview:

**Application**

Bypassing mechanical obstacles in cable routing

**Material**


Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

**Available to order:**

**F-** steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)

**E-** stainless steel (SS)

**L-** powder coating in a full range of colours (PC)



**For installation use Screw Sets SGK M6×10 or SG M6×10 and Straight Connectors LPL or LPP. Quick and convenient installation by the use of dismantled parts. This innovative solution allows for fast and safe cable laying without the need of pulling**

### Versions:

Sheet thickness: **1,0 mm**

Symbol	Width a [mm]	Catalogue number	Quantity in box	Weight 1 pc.
OPZNJ50H30	50	136331	1	0,43
OPZNJ100H30	100	136332	1	0,71
OPZNJ150H30	150	136333	1	0,95
OPZNJ200H30	200	136334	1	1,20
OPZNJ300H30	300	136335	1	1,68

### Connected products:



KGR...H30 Cable Tray    KGL...H30 Cable Tray    KGJ...H30 Cable Tray    KBJ...H30 Cable Tray    KBR...H30 Cable Tray    LPLH30 Straight Connector    LPPH30 Straight Connector    LPMPH30 Straight Connector



LPMLH30 Straight Connector    SGK... Screw Set    SM... Screw Set