

## LZKSC...H110 90° Vertical Bend - External

### Overview:

#### Application

Diversion in cable routing

#### Material

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

#### Available to order:

**F**- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)

**E**- stainless steel (SS)


**L**- powder coating in a full range of colours (PC)

**For joining fittings to cable tray use Straight Connectors for Fittings**

**LSSU... and Screw Sets SGKM8×16. Capability of creating vertical bends of any internal radius adjusted to minimum cable bending angle.**

#### FEATURES & BENEFITS:

- eye-pleasing appearance
- high mechanical properties
- even distribution of cables
- optional use of covers



### Versions:

Sheet thickness: 2,0 mm

| Symbol       | Width a [mm] | Catalogue number | Quantity in box | Weight 1 pc. |
|--------------|--------------|------------------|-----------------|--------------|
| LZKSC200H110 | 200          | 231222           | 2               | 7,35         |
| LZKSC300H110 | 300          | 231232           | 2               | 8,36         |
| LZKSC400H110 | 400          | 231242           | 2               | 9,18         |
| LZKSC500H110 | 500          | 231252           | 2               | 10,45        |
| LZKSC600H110 | 600          | 231262           | 2               | 11,59        |