

KSC...H120 Cable Tray

Overview:

Application

Cable routing in halls or on-site with limited number of supporting structures. High tray durability allows for applying spacing of supports even every 6m.



Material

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:

F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)

E- stainless steel (SS)

L- powder coating in a full range of colours (PC)

IMPORTANT! In case of large orders

- cable tray with perforated side profile

- cable tray from 2 up to 12m long

- cable tray: 1,2 and 2,5mm thick sheet.

Cable Tray adapted for installation of Cable Clamps: UKZ1, UKZ2

Versions:

Sheet thickness: **2,0 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
KSC200H120/3	3000	200	240120	2	8,46	22600
KSC200H120/6	6000	200	240121	2	8,46	22600
KSC300H120/3	3000	300	240130	2	9,36	34600
KSC300H120/6	6000	300	240131	2	9,36	34600
KSC400H120/3	3000	400	240140	2	10,26	46600
KSC400H120/6	6000	400	240141	2	10,26	46600
KSC500H120/3	3000	500	240150	2	11,16	58600
KSC500H120/6	6000	500	240151	2	11,16	58600
KSC600H120/3	3000	600	240160	2	12,06	70600
KSC600H120/6	6000	600	240161	2	12,06	70600