

KSC...H150 Cable Tray

Overview:

Application

Cable routing in halls or on-site with limited number of supporting structures. High tray durability allows for applying spacing of supports even every 6m.



Material

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:

F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)

E- stainless steel (SS)

L- powder coating in a full range of colours (PC)

IMPORTANT! In case of large orders

- cable tray with perforated side profile

- cable tray from 2 up to 12m long

- cable tray: 1,2 and 2,5mm thick sheet.

Cable Tray adapted for installation of Cable Clamps: UKZ1, UKZ2

Versions:

Sheet thickness: **2,0 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
KSC200H150/3	3000	200	270120	2	10,00	27800
KSC200H150/6	6000	200	270121	2	10,00	27800
KSC300H150/3	3000	300	270130	2	10,90	42800
KSC300H150/6	6000	300	270131	2	10,90	42800
KSC400H150/3	3000	400	270140	2	11,80	57800
KSC400H150/6	6000	400	270141	2	11,80	57800
KSC500H150/3	3000	500	270150	2	12,70	72800
KSC500H150/6	6000	500	270151	2	12,70	72800
KSC600H150/3	3000	600	270160	2	13,60	87800
KSC600H150/6	6000	600	270161	2	13,60	87800