


DSP...H100 Cable Ladder

Overview:

Application

Cable routing in halls or on-site with limited number of supporting structures. High tray durability allows for applying spacing of supports even every 8m.



Material

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:

F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)
E- stainless steel (SS)
L- powder coating in a full range of colours (PC)

IMPORTANT!

In case of large quantity orders available are:

- cable ladders with slotted side walls
 - cable ladder from 2 to 12m long
 - cable ladders of 1.2, 2.5mm steel thickness of a side wall
- Cable ladder with rungs adapted for use with Cable Clamps
UK

Versions:

Sheet thickness: 1,5 mm

| Symbol | Length L [m] | Width a [mm] | Catalogue number | Quantity in box | Weight [1m] | Effective section |
|--------------|--------------|--------------|------------------|-----------------|-------------|-------------------|
| DSP200H100/3 | 3000 | 200 | 410020 | 2 | 4,74 | 16400 |
| DSP200H100/6 | 6000 | 200 | 410021 | 2 | 4,74 | 16400 |
| DSP300H100/3 | 3000 | 300 | 410030 | 2 | 5,02 | 24600 |
| DSP300H100/6 | 6000 | 300 | 410031 | 2 | 5,02 | 24600 |
| DSP400H100/3 | 3000 | 400 | 410040 | 2 | 5,31 | 32800 |
| DSP400H100/6 | 6000 | 400 | 410041 | 2 | 5,31 | 32800 |
| DSP500H100/3 | 3000 | 500 | 410050 | 2 | 5,60 | 41000 |
| DSP500H100/6 | 6000 | 500 | 410051 | 2 | 5,60 | 41000 |
| DSP600H100/3 | 3000 | 600 | 410060 | 2 | 5,89 | 49200 |
| DSP600H100/6 | 6000 | 600 | 410061 | 2 | 5,89 | 49200 |