

DSC...H200 Cable Ladder

Overview:

Application

Cable routing in halls or on-site with limited number of supporting structures. High tray durability allows for applying spacing of supports even every 8m.



Material

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:

F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)

E- stainless steel (SS)

L- powder coating in a full range of colours (PC)

IMPORTANT!

In case of large quantity orders available are:

- cable ladders with slotted side walls

- cable ladder from 2 to 12m long

- cable ladders of 1.2, 2.5mm steel thickness of a side wall

Cable ladder with rungs adapted for use with Cable Clamps

UK

Versions:

Sheet thickness: **2,0 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
DSC200H200/3	3000	200	433320	1	10,15	37800
DSC200H200/6	6000	200	433420	1	10,15	37800
DSC300H200/3	3000	300	433330	1	10,29	57800
DSC300H200/6	6000	300	433430	1	10,29	57800
DSC400H200/3	3000	400	433340	1	10,78	77800
DSC400H200/6	6000	400	433440	1	10,78	77800
DSC500H200/3	3000	500	433350	1	11,06	97800
DSC500H200/6	6000	500	433450	1	11,06	97800
DSC600H200/3	3000	600	433360	1	11,31	117800
DSC600H200/6	6000	600	433460	1	11,31	117800