


## DST...H200 Cable Ladder

### Overview:

#### Application

Cable routing in halls or on-site with limited number of supporting structures. High tray durability allows for applying spacing of supports even every 8m.



#### Material

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

#### Available to order:

**F**- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)  
**E**- stainless steel (SS)  
**L**- powder coating in a full range of colours (PC)

#### IMPORTANT!

In case of large quantity orders available are:

- cable ladders with slotted side walls
  - cable ladder from 2 to 12m long
  - cable ladders of 1.2, 2.5mm steel thickness of a side wall
- Cable ladder with rungs adapted for use with Cable Clamps  
**UK**

### Versions:

Sheet thickness: **3,0 mm**

| Symbol       | Length L [m] | Width a [mm] | Catalogue number | Quantity in box | Weight [1m] | Effective section |
|--------------|--------------|--------------|------------------|-----------------|-------------|-------------------|
| DST200H200/6 | 6000         | 200          | 433620           | 1               | 15,05       | 37800             |
| DST300H200/6 | 6000         | 300          | 433630           | 1               | 15,19       | 57800             |
| DST400H200/6 | 6000         | 400          | 433640           | 1               | 15,68       | 77800             |
| DST500H200/6 | 6000         | 500          | 433650           | 1               | 15,96       | 97800             |
| DST600H200/6 | 6000         | 600          | 433660           | 1               | 16,21       | 117800            |