

## CTMT40H40... Support Channel

### Overview:

#### Application

Used for suspending lighting, as part of the assembly, and as construction element for installing cable trays, ladders, and Brackets WWT, WPT, WWC, WWCN, WPL, WTL, WW, WWS, WWD, WMC, and WMCN.


#### Material

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

#### Available to order:

F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)  
L- powder coating in a full range of colours (PC)

**Note: Application of Angle Fittings LCTV... allows to join support channels at various angles. Important! In case of large quantity orders available for support channel made of steel sheets 1.5, 2.5mm thick. For the assembly of support channel in combination with channel connector use Screw Sets SGK M10×20 or SG M10×20.**



### Versions:

Sheet thickness: **3,0 mm**

| Symbol      | Length L [m] | Width a [mm] | Catalogue number | Quantity in box | Height H [mm] | Weight 1 pc. |
|-------------|--------------|--------------|------------------|-----------------|---------------|--------------|
| CTMT40H40/3 | 3000         | 40           | 640130           | 2               | 40            | 9,79         |
| CTMT40H40/6 | 6000         | 40           | 640160           | 1               | 40            | 19,58        |