


KBJ...H60 Cable Tray

Overview:

Application
Cable routing

Material
Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:
F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)
E- stainless steel (SS)
L- powder coating in a full range of colours (PC)



Important!
Possibility of joining cable tray KBR..., KBL..., KBJ... and KBD... sections together through sliding one into another and connector-free assembly. Cable Tray sections of KBP... can be joined up only through the use of connectors (lack of cut in the flange at the end of side profile). Available when ordering in large quantity are 6m long tray sections. To install cable tray use Screw Sets SGK M6x12 or SG M6x12.

Versions:

Sheet thickness: 1,0 mm

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
KBJ50H60/3	3000	50	162024	12	1,53	2900
KBJ100H60/3	3000	100	162210	6	2,00	5800
KBJ150H60/3	3000	150	162215	6	2,40	8800
KBJ200H60/3	3000	200	162220	6	2,80	11800
KBJ300H60/3	3000	300	162230	4	3,60	17800
KBJ400H60/3	3000	400	161640	4	4,40	23800
KBJ500H60/3	3000	500	161650	2	5,20	29800
KBJ600H60/3	3000	600	161660	2	6,00	35800

Connected products:

