

## KZLWP...H50 Reinforced Cable Tray Integral Connector


### Overview:

**APPLICATIONS**

Cable routing.

**MATERIAL**

Steel, hot-dip galv.  
to PN-EN ISO 1461:2011 (HDG)  
Available finishes:  
E - stainless steel (SS), grade 1.4301 (AISI304)  
L - powder coating in a full range of colours (PC)



**Advantage:**

**Additional top bendings increase loading capacity and protects the cables against damage during laying**  
**For the installation use 10 sets of Screw SGKFM6x12 or SGFM6x12**

### Versions:

Sheet thickness: **1,5 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
<b>KZLWP100H50/3</b>	<b>3000</b>	<b>100</b>	<b>355710</b>	<b>6</b>	<b>3,47</b>	<b>4800</b>
<b>KZLWP200H50/3</b>	<b>3000</b>	<b>200</b>	<b>355720</b>	<b>4</b>	<b>4,81</b>	<b>9800</b>
<b>KZLWP300H50/3</b>	<b>3000</b>	<b>300</b>	<b>355730</b>	<b>4</b>	<b>6,25</b>	<b>14800</b>
<b>KZLWP400H50/3</b>	<b>3000</b>	<b>400</b>	<b>355740</b>	<b>2</b>	<b>7,68</b>	<b>19800</b>
<b>KZLWP500H50/3</b>	<b>3000</b>	<b>500</b>	<b>355750</b>	<b>2</b>	<b>9,22</b>	<b>24800</b>
<b>KZLWP600H50/3</b>	<b>3000</b>	<b>600</b>	<b>355760</b>	<b>2</b>	<b>10,66</b>	<b>29800</b>