

## KZWP...H100 Reinforced Cable Tray


### Overview:

#### APPLICATIONS

Cable routing.

#### MATERIAL

Steel, hot-dip galv.  
to PN-EN ISO 1461:2011 (HDG)  
Available finishes:  
E - stainless steel (SS), grade 1.4301 (AISI304)  
L - powder coating in a full range of colours (PC)



#### Advantage:

**Additional top bendings increase loading capacity and protects**

**the cables against damage during laying**

**To join 2 cable tray lengths firmly use either 2 pair of Straight**

**Connector LZCH100 or 1 pc of U-Shaped Connector**

**LCC...H100**

**and 16 sets of Screw SGKFM8x14 or SGFM8x14.**

### Versions:

Sheet thickness: **1,5 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
<b>KZWP100H100/3</b>	<b>3000</b>	<b>100</b>	<b>315210</b>	<b>4</b>	<b>4,11</b>	<b>9800</b>
<b>KZWP200H100/3</b>	<b>3000</b>	<b>200</b>	<b>315220</b>	<b>2</b>	<b>5,35</b>	<b>19800</b>
<b>KZWP300H100/3</b>	<b>3000</b>	<b>300</b>	<b>315230</b>	<b>2</b>	<b>6,58</b>	<b>29800</b>
<b>KZWP400H100/3</b>	<b>3000</b>	<b>400</b>	<b>315240</b>	<b>2</b>	<b>7,82</b>	<b>39800</b>
<b>KZWP500H100/3</b>	<b>3000</b>	<b>500</b>	<b>315250</b>	<b>2</b>	<b>9,05</b>	<b>49800</b>
<b>KZWP600H100/3</b>	<b>3000</b>	<b>600</b>	<b>315260</b>	<b>2</b>	<b>10,29</b>	<b>59800</b>