


PZKZWP... Cover with lock

Overview:

APPLICATIONS
 Protecting cables against damage.
 Tight cover protection against
 accumulation of dirt and dust.

MATERIAL
 Steel, hot-dip galv.
 to PN-EN ISO 1461:2011 (HDG)
 Available finishes:
 E - stainless steel (SS), grade 1.4301 (AISI304)
 L - powder coating in a full range of colours (PC)

NOTE:
 In every cover are pre-punched holes, necessary for
 dipping-in
 melted zinc (ref. hot-dip galvanizing process)
 Covers fit trays KZW... and KZLW...



POZOR!
 ŠÍRKY: 50 a 100 mm
 - 1 SYMETRICKÝ ZAMOK
 ŠÍRKY NAD: 100 mm
 - 2 ZAMKY

Versions:

Sheet thickness: 1,5 mm

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]
PZKZWP50/2	2000	50	308505	20	0,86
PZKZWP50/3	3000	50	308605	20	0,86
PZKZWP100/2	2000	100	308510	10	1,48
PZKZWP100/3	3000	100	308610	10	1,48
PZKZWP200/2	2000	200	308520	6	2,71
PZKZWP200/3	3000	200	308620	6	2,71
PZKZWP300/2	2000	300	308530	6	3,95
PZKZWP300/3	3000	300	308630	6	3,95
PZKZWP400/2	2000	400	308540	4	5,19
PZKZWP400/3	3000	400	308640	4	5,19
PZKZWP500/2	2000	500	308550	6	6,42
PZKZWP500/3	3000	500	308650	4	6,42
PZKZWP600/2	2000	600	308560	4	7,66
PZKZWP600/3	3000	600	308660	4	7,66