


CMM41H41...F Support Channel

Overview:

Application

Used for suspending lighting, as part of the assembly, and as construction element for installing cable trays, ladders, and Brackets **WWT, WPT, WWC, WWCN, WPL, WTL, WW, WWS/WWSO, WWD, WMC/WMCO, WMCN**.



Material

Steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)

Available to order:

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

E- stainless steel, lengths up to 3 m, addition CMC41H41, CMM41H41 i CMT41H41 (SS)
L- powder coating in a full range of colours (PC)

Important!

For the assembly of support channel in combination with support channel connector use Screw Sets SGKM10x20 or SGM10x25

Versions:

Sheet thickness: **2,5 mm**

| Symbol | Length L [m] | Width a [mm] | Catalogue number | Quantity in box | Height H [mm] | Weight 1 pc. |
|--------------------|--------------|--------------|------------------|-----------------|---------------|--------------|
| CMM41H41/3F | 3000 | 41 | 621330 | 8 | 41 | 6,66 |
| CMM41H41/6F | 6000 | 41 | 621360 | 8 | 41 | 13,32 |