

## KCD...H100N Cable Tray

### Overview:


**Application**  
Cable routing

**Material**  
Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

**Available to order:**  
F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)  
E- stainless steel (SS)  
L- powder coating in a full range of colours (PC)

**Important! Possibility of joining cable tray sections together through sliding one into another and connectorfree assembly.**

**Available when ordering in large quantity are 2m and 6m long tray sections. To install cable tray use Screw Sets SGK M6x12 or SG M6x12.**



### Versions:

Sheet thickness: **1,2 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
KCD100H100/3N	3000	100	110610	4	2,92	9800
KCD150H100/3N	3000	150	110615	4	3,34	14800
KCD200H100/3N	3000	200	110620	4	3,75	19800
KCD300H100/3N	3000	300	110630	2	4,58	29800
KCD400H100/3N	3000	400	110640	2	5,41	39800
KCD500H100/3N	3000	500	110650	2	6,24	49800
KCD600H100/3N	3000	600	110660	2	7,07	59800

### Connected products:

