

GDA...- 4-5P/DX/SX Koleno Horizontálne (250-2500A)

Overview:

Použitie

Slúži na zmenu smeru rovných trás.

- verzie pre 250 A až 2500 A
- v 4 a 5 pólovom prevedení
- spájanie dielov svorkovou spojkou
- krytie IP 50, s príslušenstvom možnosť dosiahnuť až IP 55



A	4P - DX				4P - SX			
	250	500	1000	2000	250	500	1000	2000
250-500	100000	100000	100000	100000	100000	100000	100000	100000
500-1000	100000	100000	100000	100000	100000	100000	100000	100000
1000-2000	100000	100000	100000	100000	100000	100000	100000	100000
2000-2500	100000	100000	100000	100000	100000	100000	100000	100000

Materiál

- zbernice - hliník
- kryt hliník
- štandardé dĺžky 500mm

Versions:

Symbol	Pól	El. prúd [A]
GDA100102	4P - DX	250
GDA100101	4P - SX	250
GDA200102	5P - DX	250
GDA200101	5P - SX	250
GDA100106	4P - DX	500
GDA100105	4P - SX	500
GDA200106	5P - DX	500
GDA200105	5P - SX	500
GDA100116	4P - DX	1000
GDA100115	4P - SX	1000
GDA200116	5P - DX	1000
GDA200115	5P - SX	1000
GDA116116	4P - DX	1250
GDA116115	4P - SX	1250
GDA216116	5P - DX	1250
GDA216115	5P - SX	1250
GDA120116	4P - DX	2000
GDA120115	4P - SX	2000
GDA220116	5P - DX	2000
GDA220115	5P - SX	2000