

## GDR...- 4-5P/DX/SX Koleno Horizontálne (100-2500A)

### Overview:

#### Použitie

Služi na zmenu smeru rovných trás.

- verzie pre 100 až 2500 A
- v 4 a 5 pólovom prevedení
- spájanie dielov svorkovou spojkou
- krytie IP 50, s príslušenstvom možnosť dosiahnuť až IP 55



A	DX 4		DX 5	
	DX	SX	DX	SX
100/102M	100/102M	100/102M	100/102M	100/102M
400	400	400	400	400
1250	1250	1250	1250	1250
1600	1600	1600	1600	1600
2000	2000	2000	2000	2000
2500	2500	2500	2500	2500

#### Materiál

- zbernice - meď
- kryt hliník
- štandardé dĺžky 500mm

### Versions:

Symbol	Pól	El. prúd [A]
GDR100102M	4P - DX	100
GDR100101M	4P - SX	100
GDR200102M	5P - DX	100
GDR200101M	5P - SX	100
GDR100102	4P - DX	400
GDR100101	4P - SX	400
GDR200102	5P - DX	400
GDR200101	5P - SX	400
GDR100106	4P - DX	630
GDR100105	4P - SX	630
GDR200106	5P - DX	630
GDR200105	5P - SX	630
GDR100116	4P - DX	1250
GDR100115	4P - SX	1250
GDR200116	5P - DX	1250
GDR200115	5P - SX	1250
GDR116116	4P - DX	1600
GDR116115	4P - SX	1600
GDR216116	5P - DX	1600
GDR216115	5P - SX	1600
GDR120116	4P - DX	2000
GDR120115	4P - SX	2000
GDR220116	5P - DX	2000
GDR220115	5P - SX	2000