


GMT...R1/2 (12kV) Rovný diel 0,6-2m (12kV)

Overview:

Použitie

Slúži na vytváranie rovných trás.

- verzie pre 12kV
- spájanie dielov skrutkami (v balení)
- krytie IP 40 až IP68



Symbol	Height H [mm]	Type	Length min.L [mm]	Length.L max.[mm]	El. prúd [A]
GMT108R2	182	A	1001	2000	800
GMT108R1	182	A	600	1000	800
GMT112R2	182	A	1001	2000	1250
GMT112R1	182	A	600	1000	1250
GMT116R2	182	A	1001	2000	1600
GMT116R1	182	A	600	1000	1600
GMT120R2	356	B	1001	2000	2000
GMT120R1	356	B	600	1000	2000
GMT125R2	356	B	1001	2000	2500
GMT125R1	356	B	600	1000	2500
GMT132R2	356	B	1001	2000	3200
GMT132R1	356	B	600	1000	3200
GMT140R2	400	C	1001	2000	4000
GMT140R1	400	C	600	1000	4000

Symbol	Height H [mm]	Type	Length min.L [mm]	Length.L max.[mm]	El. prúd [A]
GMT108R2	182	A	1001	2000	800
GMT108R1	182	A	600	1000	800
GMT112R2	182	A	1001	2000	1250
GMT112R1	182	A	600	1000	1250
GMT116R2	182	A	1001	2000	1600
GMT116R1	182	A	600	1000	1600
GMT120R2	356	B	1001	2000	2000
GMT120R1	356	B	600	1000	2000
GMT125R2	356	B	1001	2000	2500
GMT125R1	356	B	600	1000	2500
GMT132R2	356	B	1001	2000	3200
GMT132R1	356	B	600	1000	3200
GMT140R2	400	C	1001	2000	4000
GMT140R1	400	C	600	1000	4000

Materiál

- zbernice - meď
- kryt - hliník (2mm) , farbený hliník, nerez
- šírka 264 mm

Versions:

Symbol	Height H [mm]	Type	Length min.L [mm]	Length.L max.[mm]	El. prúd [A]
GMT108R2	182	A	1001	2000	800
GMT108R1	182	A	600	1000	800
GMT112R2	182	A	1001	2000	1250
GMT112R1	182	A	600	1000	1250
GMT116R2	182	A	1001	2000	1600
GMT116R1	182	A	600	1000	1600
GMT120R2	356	B	1001	2000	2000
GMT120R1	356	B	600	1000	2000
GMT125R2	356	B	1001	2000	2500
GMT125R1	356	B	600	1000	2500
GMT132R2	356	B	1001	2000	3200
GMT132R1	356	B	600	1000	3200
GMT140R2	400	C	1001	2000	4000
GMT140R1	400	C	600	1000	4000