

KSP...H100N Cable Tray

Overview:

Application

Cable routing in halls or on-site with limited number of supporting structures. High tray durability allows for applying spacing of supports even every 6m.

Material


Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:

F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)

E- stainless steel (SS)

L- powder coating in a full range of colours (PC)



IMPORTANT! In case of large orders

- cable tray with perforated side profile

- cable tray from 2 up to 12m long

- cable tray: 1,2 and 2,5mm thick sheet.

Cable Tray adapted for installation of Cable Clamps: UKZ1, UKZ2

Versions:

Sheet thickness: 1,5 mm

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
KSP200H100/6N	6000	200	220021	2	5,81	19800
KSP300H100/6N	6000	300	220031	2	6,71	29800
KSP400H100/6N	6000	400	220041	2	7,61	39800
KSP500H100/6N	6000	500	220051	2	8,51	49800
KSP600H100/6N	6000	600	220061	2	9,41	59800

Connected products:



KKSC...H100N 90°
Horizontal Bend



KKSMC...H100N 45°
Horizontal Bend



TKSC...H100N
Horizontal Tee



CZKSC...H100N
Horizontal Cross-over



LWKSC...H100N 90°
Vertical Bend -
Internal



LZKSC...H100N 90°
Vertical Bend -
External