

LZWC...H50 90° Vertical Bend - Internal

Overview:

APPLICATION

Diversion in cable routing

Material


Hot-dip galv. steel to PN-EN ISO 1461:2011 (HDG)

Available to order:

E- stainless steel (SS)

L- powder coating in a full range of colours (PC)

For joining fittings to cable tray lengths use Straight Connectors LZC...



Versions:

Sheet thickness: **2,0 mm**

Symbol	Width a [mm]	Catalogue number	Quantity in box	Weight 1 pc.
LZWC50H50	50	351905	10	1,40
LZWC100H50	100	351910	10	1,60
LZWC200H50	200	351920	6	2,26
LZWC300H50	300	351930	4	2,94
LZWC400H50	400	351940	2	3,61
LZWC500H50	500	351950	1	4,29
LZWC600H50	600	351960	1	4,96

Connected products:

KZC...H50 Cable Tray	KZLC...H50 Cable Tray with Integral Connector	LZCH50 Straight Connector	LCC...H50 U-Shaped Connector	LZGCH50 Articulated Connector	KKZC...H50 90° Horizontal Bend	KKZMC...H50 45° Horizontal Bend	TKZC...H50 Horizontal Tee
CZKZC...H50 Horizontal Cross-over	LZZC...H50 90° Vertical Bend - External	LZZMC...H50 45° Vertical Bend - External	LZWMC...H50 45° Vertical Bend - Internal	TRZC...H50 Vertical Tee - Lengthwise	RKZC...H50 Straight Reducer		